

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 October 2005 (20.10.2005)

PCT

(10) International Publication Number
WO 2005/096697 A3

(51) International Patent Classification⁷: **A41D 15/00**

(21) International Application Number:
PCT/IB2005/002379

(22) International Filing Date:
11 February 2005 (11.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/543,974 12 February 2004 (12.02.2004) US

(71) Applicant (for all designated States except US): **SANSU, LTD.** [GB/GB]; 11 Edith Terrace, Studio 4, London SW10 0TH (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **RATCLIFFE, Suzy** [GB/GB]; 11 Edith Terrace, Studio 4, London SW10 0TH (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(88) Date of publication of the international search report:

23 March 2006

[Continued on next page]

(54) Title: GARMENT LENGTH ADJUSTMENT MECHANISM



(57) Abstract: An adjustable garment includes at least one lengthwise portion, the lengthwise portion including a first inside seam (14) and a second inside seam, at least one attaching mechanism (20) fastened to each of the first inside seam and the second inside seam, and at least one receiving portion (22) positioned along a length of each of the first inside seam and the second inside seam for receiving the at least one attaching mechanism when the lengthwise portion is turned inwards.

WO 2005/096697 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.